



RONGTA

RLS1100F

Main Specifications

- Dual print modules, support label & receipt printing simultaneously
- Label printing
- Cashier function: checkout bill printing, pending order function, cumulative deletion of goods, change and wipe function, payment function, device information printing



Item

RLS1100F

PC Hardware	Item	Definition
Hardware	CPU	LPC1778FBD208
	SDRAM	8M
	Memory	512KB
Internet	Wired	TCP/IP (100M)
	WIFI	802.11 b/g/n
Keys	Turn on/off	Support
	Mylar Button	90 buttons (30 function keys , 60*2 hot keys)
External Interfaces	Cashbox	1*RJ11
	Serial	1*DB9
	Ethernet	Standard 8-pin network cable
	USB	Standard USB (2 pcs)
Power	Adapter	AC100~240V,50/60Hz
Printer Hardware	Item	Definition
Label Printing	Printing method	Direct Thermal label printing
	Printing width	58mm
	Resolution	203DPI
	Printing speed	90mm/s
	Barcode type	2/5 interleaved, 128 code , EAN13 code、GS128 ETC.
	Max.paper Width	60mm
	Maximum outer diameter	100mm
Receipt Printing	Printing method	Thermal line
	Printing width	48mm
	Resolution	203DPI
	Printing speed	60mm/s
	Paper width	58mm
	Maximum outer diameter	50mm
	FLASH	64KB
RAM	8KB	
Scales Hardware	Item	Definition
Weighing	Max.capacity	15kg 30kg
	Verification Scale Interval	2/5g 5/10g
	Minimun Capacity	40g 100g
Capacity	Safety Capacity	120%Normal weighing range
	Rated Capacity	Normal weighing range
Accuracy Class		III
Software	Item	Definition
Functions	Printing:	standard label printing;
	Weighing:	PLU hotkey, key function, Tare, special price, price change, copy, pricing,discout ETC.
	Receipt printing:	the module supports receipt printing
Packaging and Environment	Item	Definition
Accessories	■Power cord■Specification (including warranty and certificate of conformity)	
Packing	■Kraft paper■Styrofoam	
Environment	Temperture	Storage: -10℃—60℃ Working: 0℃—40℃
	Humidity	Storage: 10%—90% (Except the paper roll) Working: 5%—85%