

IP CCTV / Professional IP cameras / Uniview - Uniarch / Speed Domes

UV-UHO-P1A-M5F4D

Uniarch



Features

- Uniarch
- IP PT camera
- 1/2.7" Progressive Scan CMOS
- 5 Megapíxel
- 4 mm Lens
- 0 Lux
- IR range 30 m white light 10 m
- Autotracking
- Compression Ultra265/H.265/H.264
- RJ-45 10/100 BaseT
- Wifi IEEE802.11b/g/n
- IR Cut
- Built-in microphone
- WDR 120dB
- MicroSD 256GB
- Weatherproof IP66

Specifications

Brand	Uniarch
Image sensor	1/2.7" Progressive Scan CMOS
Maximum resolution	5 Megapixel (2880x1620)
Lens	4 mm
Main Stream rate	5MP (2880x1620)@25fps; 4MP (2560x1440)@25fps; 3MP (2304x1296)@25fps; 2MP (1920x1080)@30fps; 720P (1280x720)@30fps
Extra Stream rate	720P (1280x720)@30fps; D1 (720x576)@30fps; 640x360@30fps
Compression	Ultra 265, H.265, H.264, MJPEG
Minimum illumination	Colour: 0.005 lux (F2.1 AGC ON) 0 lux with IR on
Infrared range	30 m
Image improvements	DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card, Max 256 GB
Alarms	Does not have
Audio	Built-in microphone
Detection functions	Motion detection, Ultra motion detection, , Audio detection, Anti-tampering alarm.
Wi-Fi	IEEE802.11b/g/n
Wi-Fi frequency range	2.4 GHz ~ 2.4835 GHz
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power	DC 12V / 10W
Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP66
Dimensions	Ø118 x 118 x 199 mm
Weight	530 g