

IP CCTV / Professional IP cameras / Uniview - Uniarch / Speed Domes

UV-UHO-P2A-M3F4D

Uniarch



Features

- Uniarch
- WiFi PTZ IP Camera
- 1/3.0" CMOS
- 3 Megapíxel
- 4 mm Lens
- 0 Lux
- IR Range 30 m
- White light range 30 m
- Compression Ultra265/H.265/H.264
- RJ-45 10/100 BaseTX
- Wifi IEEE802.11b/g/n/ax
- IR Cut
- Built-in microphone and speaker
- DWDR
- MicroSD 512 GB
- Weatherproof IP66

Specifications

Brand	Uniarch
Image sensor	1/3.0" Progressive Scan CMOS
Maximum resolution	3 Megapixel (2304x1296)
Fixed lens	4 mm
Range performance	73.5 m (D), 29.4 m (O), 14.7 m (R), 7.3 m (I)
Viewing angle	90.5° (H), 44.4° (V), 111.3°(D)
Main Stream rate	3MP (2304x1296)@20fps
Extra Stream rate	640x360@20fps
Video compression	Ultra 265, H.265, H.264, MJPEG
Minimum illumination	Colour: 0.005Lux (F1.6, AGC ON) 0 lux with IR on
Infrared range	30 m
Detection functions	Motion Detection, People Detection, Audio Detection
Image improvements	DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card, Max 512 GB
Alarms	Does not have
Audio	Built-in microphone and speaker
Audio Compression	G.711U, G.711A
Wi-Fi	IEEE802.11b/g/n
Wi-Fi frequency range	2.4 GHz ~ 2.4835 GHz
Remote access	Web Browser, CMS Software (Uniarch Client), Smartphone (UNV-LINK, UNV-LINK Pro, Uniarch APP)
Power	DC 12V / 6.5W
Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP66



Dimensions	Ø110(W) x 110(D) x 151(H) mm
Weight	380 g