

UV-UHO-S2E

Uniarch



Features

- Uniarch
- PT IP Dome Camera
- 1/3" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 4 mm Lens
- 0,01 Lux
- IR Range 10m
- Compression H.265/H.264
- WIFI
- RJ-45 10/100 BaseT
- Includes Microphone and Speaker
- MicroSD card slot up to 256 GB
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Range	Uniarch
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920 x 1080)
Main Stream rate	2 Mpx (1 ~ 25 FPS)
Extra Stream rate	1080P (1 ~ 25 FPS)
Compression	H.265/H.264
WIFI	2.4G Wi-Fi (IEEE802.11b/g/n)
Lens	4 mm (86°)
Minimum illumination	0.02 Lux (Colour)
Infrared range	10 m
PTZ range	Pan 0° ~ 340°/ tilt-5° ~ 55°
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card slot up to 256 GB
Alarms	Does not have
Audio	Includes microphone and speaker
Network interface	Ethernet 10/100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Interoperability	ONVIF
Power	DC 5 V / 1 A
Temp. operation	-10° C ~ 55° C
Degree of protection	Weatherproof IP67
Dimensions	Ø80 x 121 (h) mm
Weight	185 g